

CONFIX™ WST split cable protection conduits

for cables with connectors



The CONFIX™ WST is a two piece corrugated conduit. Perfect for routing cables with or without connectors in rough environments.

In conjunction with e.g. [KVT-W90](#), a high degree of flexibility is achieved. Numerous conduit sizes can be used thanks to the wide variety of [split grommets](#) offered.

The length of the CONFIX™ WST split corrugated conduit can be customized to your application.

Defining your individual length:

Order numbers (ex.):

Length = 1.500 mm --> Order No. 31200.01500

All conduits are available by the metre (0.5 m steps).

RoHS
compliant

REACH
COMPLIANCE

Made in
Germany

Specifications

Material	Polypropylene
Operating temperature	-40 C° to 105 C°
Properties	UV-resistant

Advantages & benefits

■ Retrofits, repairs and maintenance can be done much more easily and quickly

Product types & sizes


CONFIX™ WST NW 10

Part No.	31200.xxxxx
EAN	
Package quantity	1
Nominal size	NW 10
External diameter	13,6 mm
Internal diameter	8,7 mm
Bending radius (static)	25 mm

CONFIX™ WST NW 14


Part No.	31210.xxxxx
EAN	
Package quantity	1
Nominal size	NW 14
External diameter	18,5 mm
Internal diameter	12,5 mm
Bending radius (static)	35 mm

Compatible with CONFIX™ FWS **31410, 31411**


CONFIX™ WST NW 16

Part No. **31215.xxxxx**
EAN
Package quantity **1**
Nominal size **NW 16**
External diameter **21,5 mm**
Internal diameter **16 mm**
Bending radius (static) **40 mm**

Compatible with CONFIX™ FWS **31413, 31414**


CONFIX™ WST NW 20

Part No. **31220.xxxxx**
EAN
Package quantity **1**
Nominal size **NW 20**
External diameter **25,5 mm**
Internal diameter **19,5 mm**
Bending radius (static) **45 mm**

CONFIX™ WST NW 23


Part No. **31230.xxxxx**
EAN
Package quantity **1**
Nominal size **NW 23**
External diameter **31 mm**
Internal diameter **24,2 mm**
Bending radius (static) **50 mm**

Compatible with CONFIX™ FWS **31416, 31417**

CONFIX™ WST NW 29


Part No. **31235.xxxxx**
EAN
Package quantity **1**
Nominal size **NW 29**
External diameter **35,5 mm**
Internal diameter **27,3 mm**
Bending radius (static) **90 mm**

Compatible with CONFIX™ FWS **31419, 31420**

CONFIX™ WST NW 37

Part No. **31240.xxxxx**
EAN
Package quantity **1**
Nominal size **NW 37**
External diameter **41,4 mm**
Internal diameter **31 mm**
Bending radius (static) **110 mm**

Compatible with CONFIX™ FWS **31422, 31423**

CONFIX™ WST NW 45

Part No. **31250.xxxxx**
EAN
Package quantity **1**
Nominal size **NW 45**
External diameter **54 mm**
Internal diameter **42,7 mm**
Bending radius (static) **130 mm**

Compatible with CONFIX™ FWS **31425, 31426**



Part No.	31260.xxxxx
EAN	
Package quantity	1
Nominal size	NW 70
External diameter	79,8 mm
Internal diameter	66,5 mm
Bending radius (static)	190 mm