

KEL-FG-ER | IP54 IP55 IP64 IP65

90° / IP65



IP65 모델은 24-pin 커넥터가 1 ~ 16mm (KT 1 ~ 15) 및 13 ~ 35mm (KT 16 ~ 20)의 케이블을 지원합니다. KEL-FG-ER 모델은 90° 회전 가능하고, IP54, IP55, IP64, IP65 등급을 지원합니다.

KEL-FG-ER-A 모델은 24-pin 커넥터가 1 ~ 16mm (KT 1 ~ 15)의 케이블을 지원합니다. KEL-FG-ER-B 모델은 24-pin 커넥터가 13 ~ 35mm (KT 16 ~ 20)의 케이블을 지원합니다.

모델 KEL-FG-ER-E는 24-pin 커넥터가 1 ~ 16mm (KT 1 ~ 15)의 케이블을 지원합니다.

모델은 가스켓(gasket)을 포함합니다.

IP54 	IP55 	IP64 	IP65 		


IP 등급 (EN 60529)	IP54, IP55, IP64, IP65
케이블 길이	1, 10, 16 mm, 147 mm, 80 mm
케이블 유형	UL94-V0, 24-pin
작동 온도	-40 C° to 90 C°
특징	UV-보호, 가스켓 포함, 가스켓 포함
케이블 길이	57,5 mm

특징

- 90° 회전 가능 모델
- IP54, IP55, IP64, IP65 등급
- 24-pin 커넥터 (IP65)
- EN 62444 인증 모델 포함
- 가스켓 포함

모델 사양

KEL-FG-ER-A10




EAN
000000
000000

42340
4251269328787
1
10
16 mm
147 mm
80 mm

000000
000000
000000
000000
000000

57,5 mm
57,5 mm
112 x 36 mm
4
5,5 mm
000000
10 x KT 00

KEL-FG-ER-A7




EAN
000000
000000

42341
4251269328794
1
7
35 mm
147 mm
80 mm

000000
000000
000000
000000
000000

57,5 mm
57,5 mm
112 x 36 mm
4
5,5 mm
000000
6 x KT 00
1 x KT 00

KEL-FG-ER-A4




EAN
000000
000000

42342
4251269328800
1
4
35 mm
147 mm
80 mm

000000
000000
000000
000000
000000

57,5 mm
57,5 mm
112 x 36 mm
4
5,5 mm
000000
2 x KT 00
2 x KT 00

KEL-FG-ER-B4


EAN

□□□ □
□□ □□□ □□

42344
4251269328824
1
4
16 mm
79,8 mm
80 mm

□□ □□
□□ □ □
□□□ □□
□□□ □□
□□□□ □□

57,5 mm
57,5 mm
4
5,5 mm
□□□□ □
4 x KT □□

KEL-FG-ER-B1


EAN

□□□ □
□□ □□□ □□

42343
4251269328817
1
1
35 mm
79,8 mm
80 mm

□□ □□
□□ □ □
□□□ □□
□□□ □□
□□□□ □□

57,5 mm
57,5 mm
4
5,5 mm
□□□□ □
1 x KT □

KEL-FG-ER-E5

EAN

□□□ □
□□ □□□ □□

42347
4251269328855
5
5
17 mm
147 mm
53 mm

□□ □□
□□ □□□
□□ □ □
□□□ □□
□□□ □□
□□□□ □□

38 mm
38 mm
112 x 24 mm
2
5,5 mm
□□□□ □
5 x KT □□

KEL-FG-ER-E3


EAN

□□□ □
□□ □□□ □□

42346
4251269328848
5
3
17 mm
100 mm
53 mm

□□ □□
□□ □□□
□□ □ □
□□□ □□
□□□ □□
□□□□ □□

38 mm
38 mm
65 x 24 mm
2
5,5 mm
□□□□ □
3 x KT □□

KEL-FG-ER-E2

EAN

□□□ □
□□ □□□ □□

42345
4251269328831
5
2
17 mm
73 mm
53 mm

□□ □□
□□ □□□
□□ □ □
□□□ □□
□□□ □□
□□□□ □□

38 mm
38 mm
43 x 24 mm
2
5,5 mm
□□□□ □
2 x KT □□