

ALLIO ALU-LINE



- IP20
- RoHS compliant
- REACH COMPLIANCE
- Made in Germany
- CE
- UK CA

<b>IP</b> (EN 60529)	IP20
	0.1 mm
	-20 C° to 50 C°
0.1 mm	0.1 mm

Features

- IP20
- 0.1 mm, 0.1 mm
- 0.1 mm, 0.1 mm
- 0.1 mm
- -20 C° to 50 C°
- 0.1 mm
- 0.1 mm
- 0.1 mm
- 0.1 mm
- Rittal, Hofmann, Eldon Triton 0.1 mm

Dimensions

0.1 mm, 600 mm



EAN	<b>81132</b>	0.1 mm	<b>C8</b>
	<b>4251269333</b>	0.1 mm	<b>2,5 A</b>
	<b>071</b>	0.1 mm	<b>II(0.1 mm)</b>
	<b>1</b>		
	<b>85,2 mm</b>		
	<b>24 mm</b>		
	<b>63,2 mm</b>		
0.1 mm	<b>600 mm</b>		

UL/CSA, 600 mm



EAN	<b>81232</b>	UL/CSA	<b>600 mm</b>
	<b>1</b>	C8	<b>2,5 A</b>
UL	<b>cURus (in progress)</b>	II	<b>II(UL/CSA)</b>
	<b>85,2 mm</b>		
	<b>24 mm</b>		
	<b>63,2 mm</b>		

600 mm



EAN	<b>81334</b>	C8	<b>C8</b>
	<b>4251269333</b>	2,5 A	<b>2,5 A</b>
	<b>002</b>	II	<b>II(UL/CSA)</b>
	<b>1</b>		
	<b>85,2 mm</b>		
	<b>24 mm</b>		
	<b>63,2 mm</b>		
	<b>600 mm</b>		

1500 mm



EAN	<b>81133</b>	C8	<b>C8</b>
	<b>4251269333</b>	2,5 A	<b>2,5 A</b>
	<b>088</b>	II	<b>II(UL/CSA)</b>
	<b>1</b>		
	<b>85,2 mm</b>		
	<b>24 mm</b>		
	<b>63,2 mm</b>		
	<b>1.500 mm</b>		

UL/CSA, 1500 mm



	<b>81233</b>	UL/CSA	<b>1.500 mm</b>
EAN		C8	<b>2,5 A</b>
	<b>1</b>		<b>II(UL/CSA)</b>
UL	<b>cURus (in progress)</b>		
	<b>85,2 mm</b>		
	<b>24 mm</b>		
	<b>63,2 mm</b>		

UL/CSA, 1500 mm



	<b>81333</b>	UL/CSA	<b>C8, UL/CSA</b>
EAN	<b>4251269332</b>	C8	<b>2,5 A</b>
	<b>999</b>		<b>II(UL/CSA)</b>
	<b>1</b>		
	<b>85,2 mm</b>		
	<b>24 mm</b>		
	<b>63,2 mm</b>		
UL	<b>1.500 mm</b>		