



IP20

RoHS
compliant

REACH
COMPLIANCE

Made in
Germany

CE

UK
CA

Specifikationer

IP-Klass (EN 60529)	IP20
Material	Polyamid
Brandklass	
Temperatur	-20 C° till 50 C°
Monteringstyp	Skruvmontering

Fördelar

Produkttyper och storlekar



ArtNr.	81132	Connector	C8 connector
EAN	4251269333071	type	
		Rated current	2,5 A
Antal	1	Protection	II (Protective insulation)
Längd	85,2 mm	class	
Höjd	24 mm	Färg	svart
Bredd	63,2 mm		
Length connecting cable	600 mm		

ArtNr.	81232	Length	600 mm
EAN		connecting	cable
Antal	1	Connector	C8 connector
UL-certifikat	cURus (in progress)	type	
Längd	85,2 mm	Rated current	2,5 A
Höjd	24 mm	Protection	II (Protective insulation)
Bredd	63,2 mm	class	
		Färg	svart



ArtNr.	81334	Connector	C8
EAN	4251269333002	type	connector, angled
Antal	1	Rated current	2,5 A
Längd	85,2 mm	Protection	II (Protective insulation)
Höjd	24 mm	class	
Bredd	63,2 mm	Färg	svart
Length	600 mm		
connecting			
cable			



ArtNr.	81133	Connector	C8 connector
EAN	4251269333	type	
	088	Rated current	2,5 A
Antal	1	Protection	II (Protective insulation)
Längd	85,2 mm	class	
Höjd	24 mm	Färg	svart
Bredd	63,2 mm		
Length connecting cable	1.500 mm		



ArtNr.	81233	Length connecting cable	1.500 mm
EAN		Connector	C8 connector
Antal	1	type	
UL-certifikat	cURus (in progress)	Rated current	2,5 A
Längd	85,2 mm	Protection	II (Protective insulation)
Höjd	24 mm	class	
Bredd	63,2 mm	Färg	svart





ArtNr.	81333	Connector	C8
EAN	4251269332	type	connector, angled
	999		
Antal	1	Rated current	2,5 A
Längd	85,2 mm	Protection	II (Protective insulation)
Höjd	24 mm	class	
Bredd	63,2 mm	Färg	svart
Length connecting cable	1.500 mm		

icotek[®]
smart cable management